# Ethernet Miniature Hub 9 Ports with Twisted Pair Link MS452000

## **MICROSENS**

## **Technical Specifications**

**Type** Ethernet Repeater according to the IEEE 802.3 standard

**Connectors** 8 x RJ45 modular jack crossed for end device

1 x RJ45 non-crossed for further hubs

1 x PSU connector 2,1 mm

**Data rate** 10 Mbps

**Cable type** Shielded Twisted Pair cable category 5

Max. segment length 100 m

**LED displays** Power Standby

Receive Data are received over corresponding port
Transmit Data are sent over corresponding port

Link TP- connection intact Polarity TP- wire crossed

Power supply 12 V DC / max. 800 mA


**Dimensions** 198 x 28 x 120 mm (w x h x d)

**Operating temperature** 0°C to 55°C

**Storage temperature** -20°C to 85°C

**Rel. humidity** 5% to 80% non condensing

### **Connectors**



Link 1 2 3 4 5 6 7 8

PWR O PO OLK OOOOOOOOLNK/XMT

JB OORC OOOOOOOOOPOL/RCV

**MICROSENS** 

## **Features**

Miniature Twisted-Pair-Hub with 9 Ports

- Extremely compact, ergonomic design
- Economical
- Ideal for small workgroups
- Automatic protection of the net in the case of occurring invalid segments
- LINK port for direct connection to further repeater optional BNC connection for 10Base-2 segments accessibility

## **Displays**

Colour coded LEDs indicate the status of the hub. They simplify the installation and can be used for error diagnostics within the network.

Link 1 2 3 4 5 6 7 B PWROPOOOLKOOOOOOOLNK/XMT JBOORCOOOOOOOPOL/RCV	MICROSENS
--	-----------

#### **Repeater-Status**

LED	Name	Description
PWR	Power	Standby

#### **Link Port-Status**


LED	Name	Description
PO	Wrong Polarity	TP- wire connection exchanged
LK	Link	TP- connection intact
JB	Jabber	Invalid transmission
RC	Receive	TP-data are received

#### **Port-Status**

LED	glow	blinking
LNK/XMT	TP- connection intact	Data are sent
POL/RCV	TP- wire crossed	Data are received

## **Power supply**

The repeater is powered by an external PSU 12 V of DC / a maximum of 400 mA. The power supply connector has the following reservation:



MICROSENS does not accept any liability for correctness of this information.

Because of the constant development and improvement of our products MICROSENS reserves the right to make changes without notice at any time. 9821/ba